

FOR IMMEDIATE RELEASE

14 September 2007

GEM-CRETE HF ST

Thin Topping for Parking Garages and Industrial Floors

Gemite introduces Highly Flowable Fast-Set cement topping, formulated to withstand high impact and abrasion, making it a perfect choice for industrial floors and parking decks. Gem-Crete HF ST totally waterproofs and provides a new surface for concrete suffering from surface deterioration due to improper finishing, rain, or freeze-thaw damage. Substrate cracks treatment is a part of the Gem-Crete HF ST System. The topping can be applied 1/16" to 1/4" (1.5-6 mm) thick and is available in industrial grey, light grey and white, or can be colored with suitable tints. Gem-Crete HF ST is super tough, has a high compressive and bond strengths, is easily applied, and allows traffic in 12 hours. The key advantages are:

- Superior toughness and impact resistance.
- High strength
- High abrasion resistance
- No drying shrinkage cracking
- Excellent adhesion
- Bonds to concrete and oxidized asphalt
- Easy to apply
- Can be internally colored
- Economical

For additional information, please contact:
Igor Nikolajev, P.E.

Gemite Products Inc.

160-3840 East Robinson Road, Amherst, NY 14228

Telephone: 1-888-443-6483

Fax: 1-888-443-6329

E-mail: techinfo@gemite.com

Website: www.gemite.com